




# GLT45M-PRO-20W

## FEATURES

- Compatible with 6-wire, 4-wire, and 3-wire configurations
- Operates on 220-240V input voltage
- Supports On/Off, Triac, 1-10V Knob, and DALI dimming options
- Equipped with COB LED for efficient and uniform lighting
- Designed for a 50,000-hour lifespan (L80 at 25°C)
- Adjustable with 350° rotation and 90° tilt
- Rated IP20, ideal for indoor environments




## Basic Parameters

Track System	4 wire
Input Voltage	48VDC
Dimmability	On/Off, Traic, 1-10V Knob, DALI
Light source	COB LED
luminaire Lifetime	L80, 50.000H, (Ta=25°C)
Rotation Angle	350°
Tilting Angle	90°

## Ordering Information

Beam Angle	Wattage	CRI	Luminous(lm)	CCT
15°	20W	90	1965 lm	4000K
			1785 lm	3000K
24°	20W	90	1850 lm	4000K
			1697 lm	3000K
44°	20W	90	1924 lm	4000K
			1828 lm	3000K
48°	20W	90	2015 lm	4000K
			1832 lm	3000K
60°	20W	90	1954 lm	4000K
			1775 lm	3000K

## TECHNICAL DIAGRAMS



## FIXTURES

