



TILTUX


FEATURES

- Fully Adjustable Head – Hemispherical rotation for precise directional lighting and flexible focus.
- High-Performance COB LED – Delivers uniform light with excellent lumen output across multiple wattages (15W / 25W).
- Multiple Colour Temperatures – Available in 2700K, 3000K, 4000K, and 5000K to suit varied lighting atmospheres.
- Premium Build & Heat Dissipation – Constructed from aluminium and fire-rated PC for durability and optimal thermal management.




Basic Parameters	Details	
Dimension(mm)	Ø85*186	Ø85*211
Power	15W	25W
Input Voltage	AC85-265V AC200-240V	
Lifetime	50000hrs	
IP Rating	IP20	
CCT	1-CCT: 2700K / 3000K / 4000K / 5000K	
CRI	>80	
Beam angle (°)	36° / 60°	
Finish	White & Black	
Dimmable	Dimmable option	

DIMENSIONS



BEAM ANGLE OPTIONS



Product Ordering			
CODE	COLOUR	FNISH	STOCK
TILTUX-LC15W-W	CCT(K)	WHITE	YES
TILTUX-LC25W-W	CCT(K)	WHITE	YES
TILTUX-LC15W-B	CCT(K)	BLACK	YES
TILTUX-LC25W-B	CCT(K)	BLACK	YES