



RECESSA


FEATURES

- Ultra-Slim Profile – Minimal mounting depth for seamless installation in tight ceiling spaces.
- Interchangeable CCT – Easily switch between 3000K, 4000K, and 5700K using a built-in slide switch.
- Enhanced Protection – IP54-rated LED cover for resistance to dust and moisture.
- Flicker-Free Performance – High-quality driver ensures smooth, eye-friendly light output.
- Versatile Dimming – Triac dimmable for adjustable brightness in various settings.




Basic Parameters	Details				
Dimension(mm)	Ø85*H30	Ø145*H46		Ø190*H46	
Power(W)	7	12	16	18	25
Input Voltage	198-264V				
Lifetime					
IP Rating	IP54				
CCT	1-CCT: 3000K/4000K/5000K/5700K 3-CCT: 3000K + 4000K + 5700K				
CRI	80				
Beam angle (°)	100°				
Finish	White & Black				
Dimming option	TRIAC				

DIMENSIONS



BEAM ANGLE OPTIONS



Product Ordering			
CODE	COLOUR	FNISH	STOCK
RECESSA-LC85WB	CCT(K)	B/W	YES
RECESSA-LC145WB	CCT(K)	B/W	YES
RECESSA-LC190WB	CCT(K)	B/W	YES