




AIRLUME 6060 3D




FEATURES

- Seamless 3D geometry using linear and circular corners
- Up & down or direct only light emission
- Multiple mounting options: pendant, ceiling, recessed, wall-mounted
- Colour temperature range: 2700K to 6500K + RGB
- Dimming compatibility: NON / 0-10V / DALI
- High output: up to 100 lm/W
- Available in custom powder coat & acoustic finishes



Basic Parameters	Details
Lighting direction	Up&Down, Down
Installation	Pendant , Ceiling , Recessed , wall mounted
Beam angle	PC:105° , M1:72° , M2:70°
Light efficiency	100lm/W
Profile	W60mm*H60mm
Power	20 W/m
Optic	DF , M1 , M2
CCT	2700~6500K , RGB
Dimming	NON , 0-10V , DALI
Input voltage	200-240V , 100-277V
CRI	>80 , >90 , >95


DIAGRAMS



PROFILE SECTION



COLOUR



DF | PC cover



M1 | Prismatic plates



M2 | Prismatic plates plus



LAMPS PARAMETER			
Model	Length (mm)	Power (w)	Luminous (lm)
AL6060	500	10	1000
AL6060	600	12	1200
AL6060	700	14	1400
AL6060	800	16	1600
AL6060	900	18	1800
AL6060	1000	20	2000
AL6060	1100	22	2200
AL6060	1200	24	2400
AL6060	1300	26	2600
AL6060	1400	28	2800
AL6060	1500	30	3000
AL6060	1600	32	3200
AL6060	1700	34	3400
AL6060	1800	36	3600
AL6060	1900	38	3800
AL6060	2000	40	4000
AL6060	2100	42	4200
AL6060	2200	44	4400
AL6060	2300	46	4600
AL6060	2400	48	4800



Product Ordering

CODE	COLOUR	FINISH	STOCK
AIRLUME-LCDF	CCT(K)	PC/AC	YES
FAIRLUME-LCM1	CCT(K)	PC/AC	YES
AIRLUME-LCM2	CCT(K)	PC/AC	YES



lightcore.com.au

hello@lightcore.com.au

1300 652 719

Errors and technical data are subject to change without notice.




ALIGN 10080



FEATURES


- Versatile commercial lighting system that combines custom design with high-performance LED and optic technology
- Custom diameters, radii, and lengths to turn custom lighting concepts into reality.
- Maintains light uniformity and aesthetic across standard straight and custom feature areas.
- Available with integrated DALI
- Supplied custom made for plug and play installation




Basic Parameters	Details
Size	100mm x 80mm
Input Voltage	DC24V
Luminous Efficiency	100lm/W
Max Power	35W/m
Lifetime	L80 B10 or 72,000h
Colour / CCT	2700K, 3000K, 4000K, 6000K and 6500K
Driver	Internal or External
IP Rating	IP44
CRI	8: >80, 9: >90
Finish	Aluminium / Black / White / Custom
Control	Option of DALI 2 / Trailing Edge / Non-dimmable
Mounting	Surface Mount or Suspension

Product Ordering			
CODE	COLOUR	FINISH	STOCK
AL10080-ALU	CCT(K)	ALU	YES
AL10080-B	CCT(K)	BLACK	YES
AL10080-W	CCT(K)	WHITE	YES


DIAGRAMS




Profile Section



IES instruction



INSTALLATION






ALIGN 7080





FEATURES

- Versatile commercial lighting system that combines custom design with high-performance LED and optic technology
- Custom diameters, radii, and lengths to turn custom lighting concepts into reality.
- Maintains light uniformity and aesthetic across standard straight and custom feature areas.
- Available with integrated DALI
- Supplied custom made for plug and play installation



Basic Parameters	Details
Size	70mmx 80mm
Input Voltage	DC24V
Luminous Efficiency	2000lm/m
Max Power	20W/1m
Lifetime	L80 B10 or 72,000h
Colour / CCT	3000K, 4000K
Driver	Internal or External
IP Rating	IP44
CRI	80
Finish	Aluminium / Black / White / Custom
Control	Option of DALI 2 / Trailing Edge / Non-dimmable
Mounting	Surface Mount or Suspension

DIAGRAMS



Product Ordering			
CODE	COLOUR	FINISH	STOCK
AL7080-ALU	CCT(K)	ALU	YES
AL7080-B	CCT(K)	BLACK	YES
AL7080-W	CCT(K)	WHITE	YES



LC25R-SLIMLINE

FEATURES

- 25mm slender lighting surface
- 120 LM/W high light efficiency design, lumen output up to 2375 Lm/m
- Multiple light distribution options(Diffuser, Prismatic, Round grating, Asymmetric, Block frosted diffuser) to meet variety application requirements.
- Trimless recessed design.



Basic Parameters	Details
Profile material	AL6063-T5
Colour / CCT	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
CRI	Ra80/Ra90
Finish	Silver / Black / White / Custom
Mounting	Recessed

Optical and electronic data

	200mm	600mm	1200mm	1500mm	1800mm	2400mm
Diffuser/ Prismatic	4W	12W	24W	30W	36W	48W
	400lm	1250lm	2500lm	3150lm	3750lm	5000lm
Asymmetric	4W	12W	24W	30W	36W	48W
	710lm	1425lm	2850lm	3560lm	4275lm	5700lm
Double Asymmetric	4W	12W	24W	30W	36W	48W
	710lm	1425lm	2850lm	3560lm	4275lm	5700lm

Product Ordering

CODE	COLOUR	FINISH	STOCK
SLIMLINE-S	CCT(K)	ALU	YES
SLIMLINE-B	CCT(K)	BLACK	YES
SLIMLINE-W	CCT(K)	WHITE	YES

DIAGRAMS

