



# GLT45S-PRO-28W

## FEATURES

- Compatible with 6-wire, 4-wire, and 3-wire configurations
- Operates on 220-240V input voltage
- Supports On/Off, Triac, 1-10V Knob, and DALI dimming options
- Equipped with COB LED for efficient and uniform lighting
- Designed for a 50,000-hour lifespan (L80 at 25°C)
- Adjustable with 350° rotation and 90° tilt
- Rated IP20, ideal for indoor environments



Basic Parameters	Details
Track System	4 wire
Input Voltage	48V
Dimmability	On/Off, Triac, 1-10V Knob, DALI
Light source	COB LED
luminaire Lifetime	L80, 50.000H, (Ta=25°C)
Rotation Angle	350°
Wattage	15W
CRI	90
Tilting Angle	90°

## DIAGRAMS

## FIXTURE OPTIONS

Product Ordering			
CODE	BEAM ANGLE	LUMINOUS	CCT
GLT45S-PRO-15W-14	14°	1094 lm 1000 lm	4000K 3000K
GLT45S-PRO-15W-24	24°	1105 lm 1003 lm	4000K 3000K
GLT45S-PRO-15W-38	38°	1260 lm 1118 lm	4000K 3000K
GLT45S-PRO-15W-41	41°	1180 lm 1094 lm	4000K 3000K
GLT45S-PRO-15W-64	64°	1258 lm 1149 lm	4000K 3000K

